



## A50i/A50iR INTEGRATED AMPLIFIERS



The A50i/A50iR integrated amplifiers are the successors to the highly revered 4330SE. Many would have thought it was hard to improve on the predecessor to the A50i, but improve we have! At first glance the new 50 series looks very different - indeed the sleek styling of these new Creek integrated amps make the A50i range highly desirable.

Creek however is not about looks alone – what goes on inside these amplifiers is where they stand out from the crowd. Whatever your musical preference, these Creek integrated amplifiers will satisfy the most critical of listeners. They are powerful yet subtle. You simply won't want to switch off.

Although an evolution of the 4330SE, the Creek 50 series integrated amplifiers are innovative in the true sense of the word. Using proprietary circuitry developed by Creek engineers, the A50i guarantees an exceptional level of performance. There is no doubt that these integrated amplifiers will stand the test of time like few other products in their price category.

Creek hasn't forgotten the multitude of vinyl enthusiasts and a range of optional plug-in modules is available to match both moving magnet and moving coil cartridges.

The A50i is a standard non-remote version – the A50iR has remote volume capability. The accompanying elegant handset providing remote volume control measures just 11.5cm x 5.5cm, so that it sits comfortably in the palm of the hand. With its combination of good looks, facilities and sound quality, the Creek A50i integrated amplifiers are hard to beat and will no doubt set the standard for years to come. The latest Creek series proves yet again that the best integrated amplifiers don't have to be the most expensive.

### SPECIFICATIONS

Power Output (Both Channels)	50 Watts into 8 $\Omega$
Power Output (One Channel)	60 Watts into 8 $\Omega$
Maximum Current (5mS for 3% THD)	>18 Amps
Total Harmonic Distortion	< 0.05% 20 Hz to 20 kHz
Frequency Response	3 Hz to 25 kHz – 1dB
Power Amp Slew Rate	> 40 V per $\mu$ S
Input Sensitivity (Passive Line)	450 mV line level input for 50 W
Signal to Noise Ratio (A weighted @ $\frac{2}{3}$ power)	> 100 dB
Separation (Line Input @ 1kHz)	> 60dB
Remote Control	Volume & Mute on A50iR only
Power Consumption at Idle	< 45 Watts
Power Consumption at Full Voltage	260 Watts
Power Supply Voltage	220/240 V AC 50Hz 110/115 V AC 60 Hz
Weight	
Size	

*More detailed information can be found at [www.creekaudio.co.uk](http://www.creekaudio.co.uk)*

### CREEK AUDIO LIMITED

2 Avebury Court  
Mark Road, Hemel Hempstead  
Herts HP2 7TA U.K.  
Telephone: +44 (0)1442 260146 Fax: +44 (0)1442 243766  
Email: [info@creekaudio.co.uk](mailto:info@creekaudio.co.uk) Web: [www.creekaudio.co.uk](http://www.creekaudio.co.uk)